



Walk-In LED DMS

Skyline Products' NTCIP, NEMA TS4, AASHTO, and MUTCD compliant Walk-In LED DMS offer the highest return on investment (ROI) in the industry and offer the most flexibility for communicating critical advisories to motorists moving at high speeds. These walk-in signs accommodate 3 lines of 18-inch characters and the ability to display graphics. They are designed for overhead or roadside permanent mounts. True 18-inch characters of high-quality LEDs are legible from a distance of 1,200 feet; an unrivaled industry benchmark.



Amber Walk-In DMS

- Color configurations available in 20mm, 35mm, 48mm, and 70mm pixel pitches



Full Color Walk-In DMS

- Color configurations available in 20mm, 35mm, 48mm, and 70mm pixel pitches

Features

- Reliably, legibly, and safely communicate up-to-the-minute incident, weather, construction, congestion, and public safety alerts to high-speed motorists
- Minimize agency liability and increase safety for the motorist and the technician by performing maintenance from within the sign without closing lanes
- Remotely monitor every critical component of the sign with advanced, comprehensive feedback capabilities
- Receive ITS-Grade® quality and value from any of our high-quality solutions
- Realize a high return on your agency and community investment
- Supported by Skyline Products Customer Service
- ISO 9001:2015 certified manufacturing

Skyline Walk-In LED DMS can be integrated into any existing ITS network or system.



Walk-In LED DMS

70mm Pixel Pitch

Model Number	Char. Size(s)	Font Required for Std. NEMA Char.	Lines	Pixel Layout	Char. Per Line ¹ Maximum	Optimum	Width	Height	Depth ²	Approx. Weight (lbs) ³
VMSLED-Wx-70F-27X125-xxx	18"	5x7	3	27 x 125	25	18	30' 8"	8' 6"	45.25"	4080 - 4200
VMSLED-Wx-70F-27X105-xxx	18"	5x7	3	27 x 105	21	15	26' 1"	8' 6"	45.25"	3850 - 4100
VMSLED-Wx-70F-27X090-xxx	18"	5x7	3	27 x 90	18	13	22' 8"	8' 6"	45.25"	3250 - 3500
VMSLED-Wx-70F-27X070-xxx	18"	5x7	3	27 x 70	14	10	18' 1"	8' 6"	45.25"	2600 - 2850

35mm Pixel Pitch

Model Number	Char. Size(s)	Font Required for Std. NEMA Char.	Lines	Pixel Layout	Char. Per Line ¹ Maximum	Optimum	Width	Height	Depth ²	Approx. Weight (lbs) ³
VMSLED-Wx-35F-54X250-xxx	18" 9"	10x14 5x7	3 5	54 x 250	25 50	18 36	30' 8"	8' 6"	45.25"	4080 - 4200
VMSLED-Wx-35F-54X210-xxx	18" 9"	10x14 5x7	3 5	54 x 210	21 42	15 30	26' 1"	8' 6"	45.25"	3850 - 4100
VMSLED-Wx-35F-54X180-xxx	18" 9"	10x14 5x7	3 5	54 x 180	18 36	13 26	22' 8"	8' 6"	45.25"	3250 - 3500
VMSLED-Wx-35F-54X140-xxx	18" 9"	10x14 5x7	3 5	54 x 140	14 28	10 20	18' 1"	8' 6"	45.25"	2600 - 2850

20mm Pixel Pitch

Model Number	Char. Size(s)	Font Required for Std. NEMA Char.	Lines	Pixel Layout	Char. Per Line ¹ Maximum	Optimum	Width	Height	Depth ²	Approx. Weight (lbs) ³
VMSLED-Wx-20F-96X432-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 432	27 36 54	19 27 43	30' 7"	8' 6"	45.25"	4080 - 4200
VMSLED-Wx-20F-96X400-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 400	25 33 50	18 25 40	28' 5"	8' 6"	45.25"	3980 - 4160
VMSLED-Wx-20F-96X368-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 368	23 28 42	17 23 37	26' 4"	8' 6"	45.25"	3870 - 4120
VMSLED-Wx-20F-96X336-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 336	21 28 42	15 21 33	24' 3"	8' 6"	45.25"	3525 - 3775
VMSLED-Wx-20F-96X288-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 288	18 24 36	13 18 29	21' 1"	8' 6"	45.25"	3025 - 3275
VMSLED-Wx-20F-96X240-xxx	18" 12" 8"	16x23 11x16 7x11	3 4 6	96 x 240	15 20 30	11 15 24	17' 11"	8' 6"	45.25"	2600 - 2850

¹The number of characters per line depends upon the font and inter-character spacing. ²The ventilation options varies the depth of the sign. These sign depths can range from 6" to 21" depending on this ventilation option and mounting configuration. The various ventilation options include: N = Non-Ventilated, V = Std. Ventilation, A = Adv. Ventilation. ³Weight depends upon selected options.

Rev1-10-20